

# DHT-1311XP

Home Theater System

# DENON

**100<sup>th</sup>**  
*Anniversary*  
since 1910

www.denon100.com

## 5.1-channel Home Theater System: AVR-1311: 3D video support AV Surround Receiver SYS-391HT: Powerful Speaker System

**HDMI****3D**

Personal Memory Plus

**RDS****RadioTEXT**

### AVR-1311 AV Surround Receiver

Enjoy 3D video with the full ambience of surround sound

#### New Features

- Featuring 3D pass-through technology
- Supports HDMI 1.4a with 3D, Deep Color, "x.v.Color"
- 4 x HDMI in / 1 x HDMI out (Repeater)
- Stereo Mini Jack on front panel lets you connect any portable audio player

#### State-of-the-art Denon Solutions for Maximizing Content Quality

- Fully discrete, identical quality and power for all 5 channels (110 W x 5 ch)
- Stable power supply for high-quality sound and picture playback
- High definition audio support, Dolby TrueHD and DTS-HD Master Audio
- Minimum Signal Path for clear audio and video signal
- Direct Mechanical Ground Construction, embodying concepts for thorough vibration resistance
- Compressed Audio Restorer to enhance digital music files

#### Connectivity & Future-ready Expandability

- Dock connectivity for iPod and network streaming

#### Ease-of-Use

- Comes with simple, easy-to-use remote control handset
- Three Quick Select buttons
- Sleep timer function
- Auto surround mode
- Audio level memory, capable of correcting different signal levels for each input device

#### Others

- Audio Delay function (max. 6 frames or 200 msec)
- Muting level settings (Full/-40dB/-20dB)
- Variable subwoofer crossover switching
- Binding speaker terminals for all channels for secure and easy connections
- Low power consumption 0.5 W (Standby)

### SYS-391HT Theater Speaker Package

For rich, dynamic sound you cannot get from your TV speakers!

#### SC-F391 Two way designs front speakers

- Slim front speakers, easily installed on a TV board, deliver high sound quality with rich mid to low range
- Dual 8 cm bass-mid drivers
- 2.5 cm balanced dome tweeter
- Wooden cabinet

#### SC-C391 Two way designs center speaker

- Center speaker makes movie dialogs and vocals easy to hear.
- Dual 8 cm bass-mid drivers
- 2.5 cm balanced dome tweeter
- Wooden cabinet

#### SC-R391 Surround speakers

- Compact surround speakers are easy to install, too.
- 8 cm full-range woofer
- Wooden cabinet

#### DSW-391 Subwoofer

- 100 W subwoofer gives you a powerful deep bass



## Main Specifications

### AVR-1311

#### Power amplifier section

Rated output	*THD figures are power amp stage values.
Front L/R	75 W + 75 W (8 ohms, 20 Hz - 20 kHz, THD 0.08 %) 110 W + 110 W (6 ohms, 1 kHz, THD 0.7%)
Centre	75 W (8 ohms, 20 Hz - 20 kHz, THD 0.08 %) 110 W (6 ohms, 1 kHz, THD 0.7%)
Surround L/R	75 W + 75 W (8 ohms, 20 Hz - 20 kHz, THD 0.08 %) 110 W + 110 W (6 ohms, 1 kHz, THD 0.7%)

#### Preamplifier section

Input sensitivity/impedance	200 mV / 47 kΩ/kohms
Frequency response	10 Hz ~ 100 kHz — +1, -3 dB (DIRECT mode)
S/N Ratio	98 dB (IHF-A weighted, DIRECT mode)

#### FM section

Tuning frequency range	87.5 - 108 MHz
Usable sensitivity	1.2 μV (12.8 dBf)

#### AM section

Tuning frequency range	522 - 1611 kHz
Usable sensitivity	18 μV

#### General

Power supply	AC 230 V, 50 Hz
Power consumption	330 W (Standby 0.5 W)
Dimensions (W x H x D)	434 x 166 x 381 mm
Weight	9.2 kg

### SC-F391

Type	2-way, 3-speakers, Low-leakage-flux
Frequency range	150 Hz - 22 kHz
Input impedance	6 ohms
Dimensions (W x H x D)	125 x 320 x 155 mm
Weight	2.0 kg

### SC-C391

Type	2-way, 3-speakers, Low-leakage-flux
Frequency range	150 Hz - 22 kHz
Input impedance	6 ohms
Dimensions (W x H x D)	320 x 125 x 155 mm
Weight	2.0 kg

### SC-R391

Type	Full-range, 1 speaker
Frequency range	150 Hz - 20 kHz
Input impedance	6 ohms
Dimensions (W x H x D)	125 x 180 x 155 mm
Weight	1.1 kg

### DSW-391

Type	Built-in amplifier
Frequency range	20 Hz - 150 Hz
Dynamic power	100 W
Input impedance	22 kohms
Power supply	230 V / 50 Hz
Power consumption	65 W
Dimensions (W x H x D)	280 x 356 x 410 mm
Weight	10.4 kg

## Ports

<b>In</b>	HDMI	x 4
	Component	x 2
	S-Video (Dock)	x 1
	Composite (Video)	x 3
	Analogue Audio (Tuner included)	x 6
	Digital Optical	x 1
<b>Out</b>	Digital Coaxial	x 1
	HDMI Monitor	x 1
	Component	x 1
<b>Other</b>	Composite Monitor	x 1
	Audio Preout (Surround Back L/R, SW)	x 1 (2.1 ch)
	Phones	x 1
	Dock Control Port	x 1
	FM Tuner Antenna	x 1
	AM Tuner Antenna	x 1

\* Design and specifications are subject to change without notice.  
 \* "Dolby", "Pro Logic" and the double-D symbol are trademarks of Dolby Laboratories.  
 \* DTS is a registered trademark and the DTS logos, Symbol, DTS-HD and DTS-HD Master Audio are trademarks of DTS, Inc.  
 \* HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.  
 \* iPod is a trademark of Apple Inc., registered in the U.S. and other countries.

Denon is a trademark or registered trademark of D&M Holdings, Inc.



Convenient one box master carton



**DENON Europe**  
 Division of D&M Germany GmbH  
 An der Kleinbahn 18  
 41334 Nettetal, Germany  
 Tel.: 0049 2157 1208-0  
 Fax: 0049 2157 1208-10

**DENON UK**  
 Division of D&M Audiovisual Ltd  
 First Floor, Imperial House  
 4-10 Donegall Square East  
 Belfast BT1 5HD  
 Northern Ireland

[www.denon.eu](http://www.denon.eu)

[www.denon.eu](http://www.denon.eu)

[www.denon.co.uk](http://www.denon.co.uk)